



MSR – bright vivid colors, always

MSR

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Benefits

- Optimal light collection
- Excellent color characteristics
- Brightness on stage

Features

- Single ended lamp concept
- High CRI
- Daylight Color Temperatures

Application

- Theatre stages
- Discos
- Events
- Shows

Versions





MSR 400, MSR 575/2



MSR 700 (/2), MSR 1200 (/2)

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR 1200/2.1CT/3	40 mm	10.0 mm	84 mm	86 mm	85 mm	175 mm	53 mm
MSR 1200 1CT/3	40 mm	10.0 mm	84 mm	86 mm	85 mm	175 mm	53 mm
MSR 700 1CT/8	30 mm	8.0 mm	74 mm	76 mm	75 mm	152 mm	42 mm
MSR 700/2 1CT/8	30 mm	8.0 mm	74 mm	76 mm	75 mm	152 mm	42 mm

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR 575/2	30 mm	7.0	64 mm	66 mm	65 mm	125 mm	36 mm	35 mm	34 mm
10H 1CT/4		mm							
MSR 400	23 mm	6.0	61 mm	63 mm	62 mm	112 mm	36 mm	35 mm	34 mm
1CT/4		mm							

Controls and Dimming	
Dimmable	No
General Information	
Main Application	Studio/Disco
Operating Position	UNIVERSAL

Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928077905115	MSR 400 1CT/4	6.9 A	400 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928171605115	MSR 575/2 10H 1CT/4	6.95 A	575 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928078005114	MSR 700 1CT/8	12 A	700 W
928078105114	MSR 1200 1CT/3	13.8 A	1200 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928171505114	MSR 700/2 1CT/8	11 A	700 W
928171805114	MSR 1200/2.1CT/3	13.8 A	1200 W

General Information

Order Code	Full Product Name	Life To 50% Failures		
		Cap-Base	(Nom)	System Description
928077905115	MSR 400 1CT/4	GX9.5	1000 h	Cold Strike
928171605115	MSR 575/2 10H 1CT/4	GX9.5	1000 h	Cold Strike
928078005114	MSR 700 1CT/8	G22	1000 h	-

Order Code	Full Product Name	Life To 50% Failures		
		Cap-Base	(Nom)	System Description
928078105114	MSR 1200 1CT/3	G22	800 h	Cold Strike
928171505114	MSR 700/2 1CT/8	G22	1000 h	Cold Strike
928171805114	MSR 1200/2.1CT/3	G22	800 h	Cold Strike

Light Technical

Order Code	Full Product Name	Color Code	Correlated Color Temperature (Nom)	Color Rendering Index (Nom)	Luminous Flux (Min)	Luminous Flux (Nom)
928077905115	MSR 400 1CT/4	-	5900 K	95	28500 lm	32000 lm
928171605115	MSR 575/2 10H 1CT/4	2	6990 K	70	39000 lm	49000 lm
928078005114	MSR 700 1CT/8	-	5900 K	75	48000 lm	55000 lm
928078105114	MSR 1200 1CT/3	-	5900 K	80	94000 lm	110000 lm
928171505114	MSR 700/2 1CT/8	2	7200 K	80	48000 lm	55000 lm
928171805114	MSR 1200/2.1CT/3	2	7200 K	85	80000 lm	110000 lm

Color Rendering Diagrams

